



# Comfytex Deluxe

HETEROGENEOUS VINYL

## Technical Specifications

Level of use	EN ISO 10874	23-32
Total thickness	EN ISO 24346	ca. 2,80 mm
Wear layer	EN ISO 24340	ca. 0,40 mm
Wear layer PUR treatment		SuperGuard
Total weight/m <sup>2</sup>	EN ISO 23997	ca. 1950 g/m <sup>2</sup>
Heterogeneous PVC	EN 26986	
Width	EN ISO 24341	2-3-4m
Standard Length	EN ISO 24341	ca. 30m
Weight of standard roll		ca. 121 - 182 - 242 kg
Inflammability	EN 13501	Cfl-S1
Slip resistance	EN 13893	DS
Slip restraint	DIN 51130	R10
Thermal conductivity	EN ISO 10456	0,25 W/(m.K)
Thermal resistance	EN ISO 12664	0,0104 (m <sup>2</sup> .K/W)
Acoustic insulation	EN ISO 717-2	ΔLw 17 dB
Underfloor heating	EN 12524	Suitable
Resistance to chemical	EN ISO 26987	Very good
Warranty years	DOMESTIC	15 years
	COMMERCIAL	5 years

05/2019

The warranty covers manufacturing defects and premature wear in the event of normal use

